100 Line

Variant Factory Pack



Application:

Mixture of 100 Line mixed tinters with mixing clear 100-M 10 / 100-M 20.

Please observe the mixing ratio on the label.

Mixture will keep for six months when stored in closed plastic containers or cans coated inside.

Paint System

Please see Glasurit Know How module "Glasurit 100 Line".

2:1

Mixing Ratio

100 % by volume

100 Line Factory pack

Reducer

50 % by volume

100-F 5 (acc. to mixing formula)

Stir IMMEDIATELY after adding!

Application:

Compliant gravity-feed spray

🕌 HVLP spray gun

Application pressure

2 bar

Nozzle size

1.3-1.4

Number of spray coats

1 full coat + 1 "Finish coat" applied wet-on-wet

Flash off at 20°C

Flash off until the surface is completely mat after the "Finish coat".

Film thickness

10-15 μm

Application Remark

Spraying pressure = inlet pressure

The setup depends on the spray gun supplier, please refer to the Glasurit Know How module "BASIC

KNOWLEDGE - BODYSHOP EQUIPMENT" for detailed information.



Infrared (short wave)

Surface temperature 40 - 50°C (max. 60°C) until mat surface and cooling.

Safety advice:

The products are suitable for professional use only. It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

100 Line

Variant Factory Pack



Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

The products are suitable for professional use only. It cannot be ruled out that this product contains particles < 0.1 μm .

2004/42/IIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.