

90-IC 440

Interior Color System Metallics/Solids/Pearl Effects



A brand of BASF –
We create chemistry

- Application:** Reproduction of mat or silky mat direct-gloss finishes (to which no clear coat will be applied) from the 90 Line mixing system.
- Remarks:**
- Mixing formulas with 90-IC 440 mixing clear and mixing bases are available to cover the whole range of colours needed in automotive refinishing.
 - Substrates/Pre-treatment:
Solvent-resistant old paintwork, e-coated substrates,
Glasurit 285- or 801- primer fillers
Clean surfaces with Glasurit waterborne cleaner (base/topcoat) / sand with P400 - P500 / clean again with Glasurit waterborne cleaner (base/topcoat).
For e-coated substrates that are difficult to reach, cleaning with Glasurit waterborne cleaner (base/topcoat) is sufficient.
 - Prime bare metal areas with Glasurit primer fillers.
 - Mixing formulas that contain 90-M 5, 93-E 3, 11-E waterborne mixing bases or mixing base concentrates 80-M cannot be used with 90-IC 440.



Spreading rate 130 m²/l at 1 µm



Mixing Ratio 100 % by volume 90- Metallics/Solids (Replace 90-M4 by 90-IC 440 in the mixing formula.)



Hardener 5 % by volume 93-IC 330



Reducer 50 % by volume 352-91, -50, -10, -216, -40

Potlife at 20°C 4 h

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(e)(840)839: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 839 g/litres.



The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

90-IC 440

Interior Color System Metallics/Solids/Pearl Effects



A brand of BASF –
We create chemistry

Application:	 Compliant gravity-feed spray gun	 HVLP spray gun
Application pressure	2 bar	2-3 bar
Nozzle pressure		0.7 bar
Nozzle size	1.3-1.4 mm	1.3 mm
Number of spray coats	2	
Flash off at 20°C	Approx. 5 min. after each spraycoat.	
Film thickness	10-15 µm	

Drying Remark	
	Drying at 20 °C: 15 min. dust-free and ready for masking 3 h ready for assembly
	Drying at 60 °C: 20 min. ready for assembly

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(e)(840)839: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 839 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.