

360-4

Metal Cleaner



A brand of BASF –
We create chemistry

Application:

360-4 is used to:

- Remove oil and grease (easily, quickly and thoroughly).
- Clean bare metal panels before and after sanding.

Remarks:

- Apply Glasurit 360-4 to a clean cloth/rag.
- Clean e-coated panels prior to sealing.
- Wipe off surface contaminants, sanding residue, oil or grease.
- In the case of hard to remove materials, multiple cleanings may be necessary with a new clean cloth/rag.
- Does not contain any acidic components providing corrosion resistance.
- Not intended to be used on primer or other paint components because of its aggressiveness.
- Also available in Aerosol.
- **NOTE:** Glasurit 360-4 Metal Cleaner needs to be reduced with Glasurit 352-45 Reducer to meet VOC regulations in some areas. Refer to the Glasurit VOC wall chart for the specific AQMD of concern for the correct reduction ratio and any restrictions as to use and quantity limitations. Available reduction mix ratios and corresponding RFU VOC values are as follows:
 90 parts by volume 360-4
 10 parts by volume 352-45
 VOC ready for use: 755 g/l (6.3 lbgal)

VOC ready for use	808 g/l	6.8 lb/gal
--------------------------	---------	------------



Mixing Ratio

Ready for use

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

Safety advice:

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.