

# 522-322

## Flexible Gloss Reducing Additive



A brand of BASF –  
We create chemistry

**Application:**

Flexible gloss reducer for 22-Line and 923- Clearcoats

**Remarks:**

- Not for use in pre-flatten clearcoats.
- Prepare only the quantity of paint or clear that will be used the same day because the gloss level may change when the mixture is stored.
- Stir well after adding 522-322.
- May be used in combination with Glasurit Texture Additive 522-345.
- May be used on plastic parts without the addition of Elastifier Additive 522-111 or Low VOC Elastifier Additive 522-333.
- For additional technical information, refer to the relevant 923- clearcoat or 22-Line technical data sheets.

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

---

**Safety advice:**

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.