

# 541-30

Universal Cleaner for Plastics



A brand of BASF –  
We create chemistry

**Application:**

541-30 is used to clean:

- Raw plastic substrates
- This should not be used on primers because of its aggressive nature. This can cause swelling and wrinkling of both bumper and refinish primers.

**Remarks:**

- Clean areas with lint free cloth and 541-30, then wipe dry with a lint free cloth. **Allowing cleaner to flash completely for at least 15 minutes under ventilation is critical for a trouble free repair.**
- Please consult Glasurit Plastic Preparation guide for detailed information.
- Also available in aerosol.
- **NOTE:** Glasurit 541-30 Universal Cleaner for Plastics needs to be reduced with Glasurit 352-45 Reducer to meet VOC regulations in some areas. Refer to the Glasurit VOC wall chart for the specific AQMD of concern for the correct reduction ratio and any restrictions as to use and quantity limitations. Available reduction mix ratios and corresponding RFU VOC values are as follows:

93:7 - VOC ready for use: 775 g/l (6.5 lbgal)  
 93 parts by volume 541-30  
 7 parts by volume 352-45

---

<b>VOC ready for use</b>	795 g/l	6.6 lb/gal
--------------------------	---------	------------

---



**Mixing Ratio**

Ready for use

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

---

**Safety advice:**

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.