

# 541-5

## Silicone and Tar Remover



A brand of BASF –  
We create chemistry

**Application:**

541-5 is used:

- For cleaning the substrate before the application of 2K Primer Surfacer.
- For cleaning after finish sanding of the primers.
- As a cleaning agent for 22-, 55-, 90-Line systems.

**Key Features:**

- Clean areas with lint free cloth and 541-5, then wipe dry with a lint free cloth.
- Also available in aerosol.

---

<b>VOC ready for use</b>	779 g/l	6.5 lb/gal
--------------------------	---------	------------

---



**Mixing Ratio**

Ready for use

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

---

**Safety advice:**

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.