563-808

Sand Fix Paste



Application:

Glasurit Sand Fix Paste is a wax and silicone free sanding paste. It is used to prepare panels that are to be blended in to. It eliminates sanding blend-in areas with fine sandpaper. Sand Fix Paste is water thinnable.

Remarks:

- Wash area to be blended with soap and water followed by cleaning with 541-5 Silicone and Tar Remover.
- Apply Sand Fix Paste to a fine scuff pad (grey or white) that has been wet with water. Rub entire area
 with pad and paste until a uniform dull finish is achieved.
- Wash off residue with water. Be sure to remove all traces of Sand Fix Paste from moldings, etc. Check for any spots that may have been missed, and repeat if necessary.

VOC ready for use

30 g/l

0.3 lb/gal



Mixing Ratio

Ready for use

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

Safety advice:

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.