580-100

Antisilicone additive



A brand of BASF – We create chemistry

Application: Key Features:

Remarks:

Fisheye eliminator. Used to avoid craters caused by silicone.

Use only when **absolutely** necessary. Use as little as possible - do not exceed a maximum of 5% (by vol.).

- For use in 22-Line and clearcoats only.
- Use 580-100 only outside of the spray booth.
- · Throw out rags contaminated with fisheye eliminator immediately.
- If 580-100 is in the first coat, then it must be added to following coats (minimum of same amount).



Mixing Ratio

Add 2% to max. 5% (by volume) of 580-100 to the RFU topcoat.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < $0.1 \,\mu m$.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements. 11/2022