

700-10

Waterborne Degreaser



A brand of BASF –
We create chemistry

- Application:** To clean surfaces to be refinished. Removes silicone, grease and wax residues from surfaces as well as mold release agents from plastic surfaces. When cleaning plastic surfaces, the cleaner produces an anti-static effect and thus reduces dust settling.
- Key Features:** Good cleaning properties. Anti-static effect (for plastics refinishing).
- Remarks:**
- Soak a lint-free cloth with 700-10 and wipe the surfaces to be refinished or spray 700-10 onto the surface to be refinished and wipe them with a lint-free cloth.
 - Wipe dry immediately after use.
 - **NOTE:** Glasurit 700-10 Waterborne Degreaser needs to be reduced with distilled / deionized water to meet VOC regulations in some areas. Refer to the Glasurit VOC wall chart for the specific AQMD of concern for the correct reduction ratio and any restrictions as to use and quantity limitations. Available reduction mix ratios and corresponding RFU VOC values are as follows:

1:1 - VOC ready for use: 95 g/l (0.80 lbgal)
100 parts by volume 700-10
100 parts by volume Distilled / Deionized Water

1:2 - VOC ready for use: 64 g/l (0.53 lbgal)
100 parts by volume 700-10
200 parts by volume Distilled / Deionized Water

1:3 - VOC ready for use: 48 g/l (0.40 lbgal)
100 parts by volume 700-10
300 parts by volume Distilled / Deionized Water

1:7 - VOC ready for use: 24 g/l (0.20 lbgal)
100 parts by volume 700-10
700 parts by volume Distilled / Deionized Water

VOC ready for use 180 g/l 1.5 lb/gal



Mixing Ratio

Ready for use

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

Safety advice:

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.