

700-7

Coagulating Powder



A brand of BASF –
We create chemistry

Application:

When using waterborne products such as:

- Glasurit® 90 Line Basecoat, Metallics/Solids
- Glasurit® 176-72 1K Waterborne Primer Surfacer
- Glasurit® 1109-1240/4 Textured Stone Chip Protector, Black
- Glasurit® 1109-1240/6 Smooth Stone Chip Protector, Black

The water used to clean working tools should be collected in suitable containers.

These containers must not get in touch with solvents.

Use of 700-7 Coagulating Powder:

- Add 2 or 3 scoops of 700-7 Coagulating Powder (approx. 75 g) per about 10 liters waste water (**scatter** the powder to distribute the particles evenly and to increase efficiency) and stir briefly.
- After a short interval, the solids will start to coagulate and can then be separated from the liquid by filtering, for example through filter mats or appropriate sieves (with a mesh size of about 80-100 microns).
- When the contaminant concentration in the waste water is very high (i.e., when the water has not become clear after about 15 minutes), add more 700-7 Coagulating Powder. There is **no** risk of overdosing with 700-7.
- The coagulated substance must be disposed of according to hazardous waste regulations. The clear, aqueous phase may be used to clean spray equipment or disposed of according to water waste regulations. When you are not sure, consult the competent local authorities. **DO NOT DISCHARGE INTO PUBLIC SEWAGE SYSTEM.**

Remarks:

- Glasurit® 700-7 Coagulating Powder is used to precipitate solids from the water used to clean working tools with which water-based products were processed.
- Once the coagulated substance has been separated, the clear, aqueous phase can be used again for pre-cleaning sprayguns, which are finally rinsed with fresh tap water.

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

Safety advice:

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.