

# 801-72

Epoxy Primer Filler - Grey - as a primer



A brand of BASF –  
We create chemistry

- Application:** Primer
- Key Features:** Good corrosion protection on bare metal, galvanized steel and aluminum.
- Remarks:**
- Chromate-free
  - Primer on galvanised substrates for 1006-26 and for 285- primers.
  - Minimum temperature for application and air drying: +60°F / 15°C.
  - May be used as primer under Glasurit® 839- body fillers, Glasurit® 1006-26 (after 3 hours at 68°F / 20°C or 30 minutes at 140°F / 60°C) and certain 285- series primer fillers.

---

**VOC ready for use**                      540 g/l                      4.5 lb/gal

---

**4:1:1**



**Mixing Ratio**

100 parts by volume                      801-72



**Hardener**

25 parts by volume                      965-60



**Reducer**

25 parts by volume                      352-91, -216



**Spray viscosity at 68°F / 20°C**

DIN 4:                      18-20 s

**Potlife at 68°F / 20°C**                      8 h

---

**Application:**



**Compliant gravity-feed spray gun**



**HVLP spray gun**

**Nozzle pressure**

10 psi

**Nozzle size**

1.3-1.4 mm

**Number of spraycoats**

1

**Flash-off at 68°F / 20°C**

10-20 min

**Film thickness**

0.6-0.8 mil

---

**Safety advice:**

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.

# 801-72

Epoxy Primer Filler - Grey - as a primer



A brand of BASF –  
We create chemistry

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document

---

## Safety advice:

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous and should be used according to label directions and technical data information. Appropriate respiratory protection should be worn at all times while products are in use - read product label and Safety Data Sheet (SDS) for specific details. Statements and methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only and are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.