

A-R-140

Eco Balance reducer, extra slow



A brand of BASF –
We create chemistry

| | |
|----------------------|---|
| Zastosowanie: | This product is used in AraClass clear coat materials. |
| Główne cechy: | Use reducer A-R-140 only in combination with A-H-430 / A-H-440 Eco Balance top coat hardener and with very high ambient temperatures and infrared drying systems. |
| Uwagi: | Mixing ratio / Application: As specified in the technical data sheet of the product in which A-R-140 is being used. |



Wskazówka bezpieczeństwa:

Produkty tylko do użytku profesjonalnego. Nie można wykluczyć, że produkt ten zawiera cząstki o wielkości < 0,1 µm.

Dane zawarte w tej publikacji bazują na obecnym stanie wiedzy i doświadczeniu. W związku z tym, że na ostateczny efekt lakierowania ma wpływ wiele czynników, osoba przeprowadzająca naprawę powinna wykonywać własne badania i testy. Podane tu informacje nie stanowią również żadnej gwarancji właściwości poszczególnych produktów, jak również nie przesądzają, że dany produkt nadaje się do konkretnego zastosowania. Wszelkie opisy, rysunki, zdjęcia, dane, proporcje itp. podano tylko jako ogólne wskazówki; mogą się one zmienić bez wcześniejszego powiadomienia, co nie stanowi naruszenia specyfikacji produktu. Ostatnia wersja zastępuje wszystkie poprzednie. Można ją pobrać z naszej strony internetowej www.glasurit.com lub otrzymać bezpośrednio od dostawcy. Obowiązkiem użytkownika naszych produktów jest przestrzeganie wszelkich obowiązujących w tym zakresie norm prawnych.