

# G-A-990

Matting agent



A brand of BASF –  
We create chemistry

- Application:** Matting additive.
- Key Features:** Additive that enables the user to reduce the gloss level of Glasurit topcoats and clear coats. Please see the variant TDS for specific usage instructions. After mixing, can also be applied on plastics without the need for additional flex additives.
- Remarks:**
- Prepare only the quantity of paint that will be used the same day because the gloss level may change when the mixture is stored.
  - Stir immediately after adding Glasurit G-A-990 Matting Agent.
  - G-A-990 must not be used in mixing shelves.

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

---

**Safety advice:**

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.glasurit.com](http://www.glasurit.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.