

185-66/05

1K-filler, light grey



A brand of BASF –
We create chemistry

- Application:** 1K Filler supplied in an aerosol can for use in automotive refinishing, available in the gray shade variants 00, 02, 05 and 07.
- Filler for sand-throughs
 - Filler suitable for spot repair
- Key Features:** Can be used on old paintwork and sand-throughs.
- Remarks:** Filler with coloring properties. Sand-throughs to the bare metal must be primed before the use of 185-66.

Handling



Do not use deformed aerosol cans. While shaking the can, do not strike against solid objects. During shaking, the mixing balls are released. Avoid bumps, friction and impact.



Shake vigorously for 2 min. before use.



Number of spray coats: 1 - 2
Flash off at 20°C: approx. 5 - 10 min. between spraycoats
Film thickness: 15-30 µm



Drying at 20°C	1 h
Drying at 60°C	30 min

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIB(e)(840)673: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 673 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.