839-70K

Universal body filler



A brand of BASF – We create chemistry

Application: Key Features:		Coarse and fine body filler High solids content; universally suitable for use on steel sheet, galvanised steel, aluminium; fast drying easy to sand, good adhesion							
					Remarks:		 Mix body filler and red hardener paste well before use (homogeneous colour, no marble effect). Do not exceed 3% of hardener. Excess peroxide will cause discoloration in the finish. 		
	Mixing Ratio	100 % by weight	839-70K (dispenser)						
Ĩ	Hardener		948-52 addition of hardener depending on h	nardener cartridge					
∏s	Spray viscosity at 20°C	DIN 4:	Potlife at 20°C 5 min						
\frown									
\bigcirc	Drying at 20°C	20-30 min							
\bigcirc	Infrared (short wave)	4 min							
ìR	Infrared (medium wave)	5-10 min							
<u>s</u> e	Orbital sanding, dry	P80/150 581-90 Guide Coat P240 body-filled area and old paintwork							
9.:	orbital saliulity, ury								

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 $\mu m.$

2004/42/IIB(b)(250)180: The EU limit value for this product (product category: IIB.b) in ready to use form is max 250 g/litre of VOC. The VOC content of this product is 180 g/litres

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany