

Glasurit® Hardener VOC

G / Z

Application: • Hardeners for VOC-compliant (420 g/l) clears and topcoats

Properties: • 929-33 VOC Hardener normal
• 929-31 VOC Hardener fast
• 929-34 VOC Hardener slow

Hardeners for VOC-compliant clears 923-610, -625,- 630, -645,
22 Line HS 2K Topcoat VOC MC600

Remarks: • 929-63 VOC Hardener normal
• 929-61 VOC Hardener fast
• 929-64 VOC Hardener slow
• Seal cans with left-over material carefully!
• Hardeners are sensitive to humidity!
• See Technical Information sheets for base products.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

