

100-E 5

Reducer



A brand of BASF –
We create chemistry

Application:

Reducer for 100 Line

Key Features:

For both, effect and solid colors (with 100-M 10 / 100-M 20), 100-E 5 Reducer is used. The mixing ratio of basecoat to reducer is 2:1 by volume. Alternatively, you can use the computerized scales with Profit Manager to adjust the material in the usual manner by weight. It is important to mix the mixing bases and the mixing clear and stir before the reducer is added. After adding the reducer, the ready for use material has to be stirred again.

With the exchange of the Mixing clears 100-M 10 and 100-M 20 to 100-M 10X and 100-M 20X as well the reducer has to be exchanged. The corresponding reducer is 100-E 5X.

Remarks:

Please refer to the Glasurit Know How module "Glasurit 100 Line" for further details and information about application processes.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.