

100-MB 50

Blending clear for 100 Line



A brand of BASF –
We create chemistry



- Application:** The function of Blending clear 100-MB 50 is to optimize the alignment of special-effect particles in blending areas. When the basecoat is applied in the blending area, the effect particles of the overspray can align to only a limited extent. If Blending clear 100-MB 50 is applied to the blending area beforehand, it absorbs the basecoat overspray and the effect particles contained in the overspray can align as in a coherent basecoat applied wet. This prevents possible shadows resulting from improperly aligned effect particles, including sanding scratches.
- Key Features:** The Blending clear 100-MB 50 is ready for use and does not have to be adjusted with a separate reducer.
- Remarks:** Blending clear 100-MB 50 is never flashed-off until mat before the blend-in repair with 100 Line has been completed. For blend in repairs which have to be performed with high temperature or low humidity, the Blending clear 100-MB 50X can be used instead of 100-MB 50, as long as the X mixing clear and reducer is also used with the basecoat.



Paint System

Please see Glasurit Know How module "Glasurit 100 Line".

Material is ready for use. Just shake the material before use.

Application:	 Compliant gravity-feed spray gun	 HVLP spray gun
Application pressure	bar	2
Nozzle size		1.3-1.4
Number of spraycoats		1 full coat + 1 "Finish coat" applied wet-on-wet
Flash-off at 20°C	min	Blending clear 100-MB 50 is never flashed-off until mat before the blend-in repair with 100 Line has been completed.
Film thickness	µm	10-15
Application Remark	Spraying pressure = Inlet pressure The setup depends on the spray gun supplier, please refer to the Glasurit Know How module "BASIC KNOWLEDGE – BODYSHOP EQUIPMENT" for detailed information.	

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

100-MB 50

Blending clear for 100 Line



A brand of BASF –
We create chemistry

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(d)(420)249: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 249 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany

06/2020