






Glasurit® 1K Anti-corrosive Primer

G / P

- Application:** Primer for automotive refinishing
- Properties:** 1-pack primer supplied in an aerosol can
- Very good corrosion protection on steel, galvanised steel and aluminium
 - Weldable

	Application	Primer
	Paint system	
		Spreading rate:
	Shaking	2 min.
	Note	Do not use deformed aerosol cans. While shaking the can, do not strike against solid objects. During shaking, the mixing balls are released. Avoid bumps, friction and impact.
	Number of spraycoats	1 - 2
	Film thickness	15-20 microns
	Flash-off at 20°C	approx. 10 min.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(e)(840)685: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 685 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

