





A-C-20



Variant with A-A-12 Eco Balance air drying additive



A brand of BASF –
We create chemistry

Application: A-C-20 Eco Balance clear coat, universal with A-A-12 Eco Balance air drying additive.
Key Features: Using A-A-12 will allow for a dust-free surface more quickly. Sandability, polishability and readiness for assembly will be significantly improved.
Remarks: Use additive A-A-12 at room temperature > 20°C only.
 Ambient temperature and film build can greatly affect the drying behavior.

		3:1:1			
	Mixing Ratio	100 % by volume	A-C-20		
	Hardener	33 % by volume	A-H-410 Eco Balance top coat hardener, fast		
	Reducer	33 % by volume	A-A-12 Eco Balance air drying additive		
	Spray viscosity at 20°C	DIN 4:	18-21 s	Potlife at 20°C	45 min

Application:		 Compliant gravity-feed spray gun	 HVLP spray gun
Application pressure	bar	2	2
Nozzle pressure	bar		0.7
Nozzle size		1.3-1.4	1.3
Number of spray coats		1 ½ spray coats (no flash-off between coats required)	
Flash off at 20°C	min	No flash-off before oven drying.	
Film thickness	µm	40-50	

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

A-C-20

Variant with A-A-12 Eco Balance air drying additive



A brand of BASF –
We create chemistry



Drying at 20 °C	3-4 h
Drying at 40 °C	15-20 min **
Drying at 60 °C	10-15 min **
Drying Remark	** Polishable after 1 h. Waiting time at room temperature after surface drying in the oven.



Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.