A-C-20





Variant with A-R-140 Eco Balance reducer, extra slow

Application: A-C-20 Eco Balance clear coat, universal with A-R-140 Eco Balance reducer, extra slow.

Use reducer A-R-140 only in combination with A-H-430 / A-H-440 Eco Balance top coat hardener and **Key Features:**

with very high ambient temperatures and infrared drying systems.

3:1:1

A-C-20 **Mixing Ratio** 100 % by volume

A-H-430, -H-440 Hardener

33 % by volume Eco Balance top coat hardener

A-R-140 Reducer 33 % by volume

Eco Balance reducer, extra slow

Spray viscosity at 20°C DIN 4: 18-21 s Potlife at 20°C 2 h

Compliant gravity-feed ₩ HVLP spray gun **Application:** spray gun 2 **Application pressure** bar Nozzle pressure bar 0.7 Nozzle size 1.3-1.4 1.3

Number of spray coats

1 1/2 spray coats (no flash-off between coats required)

Flash off at 20°C	min	No flash-off before oven drying.
Film thickness	μm	40-60
Application Remark		Alternatively: 2 spraycoats with app. 3-5 min. intermediate flash-off between the spraycoats.

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < $0.1 \mu m$.

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

A-C-20





Variant with A-R-140 Eco Balance reducer, extra slow



Drying at 60 °C 25 min



Infrared (short wave) 10 min



Safety advice:

The products are suitable for professional use only. It cannot be ruled out that this product contains particles < 0.1 μ m.

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.