




A-C-90



Eco Balance clear coat, extra mat



A brand of BASF –
We create chemistry

Application: AraClass - Eco Balance clear coat for Glasurit waterborne basecoats.
Key Features: Eco effectiveness clearcoat - extra mat.
 Required for the repair of mat OEM finishes.
Remarks: Stir well before use.
 Mix with A-C-92 Eco Balance mat clear coat in order to achieve desired gloss level.
 A-C-90 must not be used in mixing shelves.

		2:1		
	Mixing Ratio	100 % by volume	A-C-90	
	Hardener	50 % by volume	A-H-490 Eco Balance top coat hardener, mat	
	Spray viscosity at 20°C	DIN 4: 18-22 s	Potlife at 20°C	2 h

Application:		 Compliant gravity-feed spray gun	 HVLP spray gun
Application pressure	bar	2	2
Nozzle pressure	bar		0.7
Nozzle size		1.3-1.4	1.3
Number of spray coats		2	
Flash off at 20°C	min	Flash off until mat between spraycoats and before stoving. After the first spraycoat, allow to flash off for 10 – 15 min, after the second spraycoat for 15 – 20 min. Do not flash off for more than 25 minutes after each spraycoat.	
Film thickness	µm	40-50	

Safety advice:

The products are suitable for professional use only.
 It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIIB(e)(840)700: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 700 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

A-C-90

Eco Balance clear coat, extra mat



A brand of BASF –
We create chemistry



Drying at 20 °C 8 h



Drying at 60 °C 30 min



Infrared (short wave) 10 min



Safety advice:

The products are suitable for professional use only.
It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/IIB(e)(840)700: The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product is 700 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.