





Glasurit® UV Body Filler

G / BF

- Application:** Fine body filler
- Properties:** Universally applicable on steel, galvanised steel, aluminium, e-coated parts, old paintwork, and all coatable plastic add-on parts.
The high solids fine body filler convinces with fast drying ability, excellent sandability and good anti-corrosive properties. They are coupled with good finish qualities.
Especially developed for the repair of small damages and scratches, to achieve a repaired surface without pores.
- Remarks:**
- do not use in direct sunlight
 - do not expose to sunlight on storage

	Application	Fine body filler
	Paint system	S 3, S 3a, S 9.5, S 15, S15a
	Mixing ratio	The material is ready for use.
	Film thickness	max. 800 µm
	UV drying	5 min. (UV-A -> min. 6 mW/cm²) By using LED lamps, the drying time can be reduced due to their higher intensity in the decisive wavelength range. This must be checked individually.
	Sanding: orbital sander	P80/150 581-90 guide coat P240/320 putty area and old paintwork

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

2004/42/II(b)(250)239: The EU limit value for this product (product category: IIB.b) in ready to use form is max 250 g/litre of VOC. The VOC content of this product is 239 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

