

523-15E Eco Balance

Racing additive



A brand of BASF –
We create chemistry

| | |
|----------------------|---|
| Application: | Drying accelerator for Glasurit standard clears (VOC-compliant and non-VOC-compliant), 22 Line, 22 Line VOC, 22 VOC MC600 and 285- HS-Primerfiller / Filler |
| Key Features: | <ul style="list-style-type: none">• Reduction of drying times• Improves surface drying and curing performance as well as tape resistance |
| Remarks: | No add of 523-15E Eco Balance Racing Additive in 285- Primerfiller / Filler at temperatures > 25°C possible, due to too short potlife |

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.



Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.